

PERFORMANCE DATA SHEET for ULTF4PLUS



Operating Parameters

Temperature: 39°F (4°C) - 113°F (45°C)
Pressure Range: 30 psi (2.1 kg/cm²) – 60 psi (4.2 kg/cm²)
Flow Rate: 8.0 gpm – 12 gpm
Estimated Rated Capacity @ 8 gpm = 30,000 gallons
Estimated Rated Capacity @ 10 gpm = 24,000 gallons
Estimated Rated Capacity @ 12 gpm = 20,000 gallons
Model Number: **ULTF4PLUS**

Replacement Filter Model Numbers:

Filter Location in Sump	Filter Model Number	Filter Description
#1	ULTF4-FILTER1	Particulate & Scale Reduction, 5 micron
#2	ULTF4-FILTER2	Micronguard
#3	ULTF4-FILTER3	PFAS and Chlorine Reduction, 5 micron

The in-family POE systems (ULTRAFILTR10PLUS and ULTRAFILTR20PLUS) have been tested and certified by IAPMO according to NSF/ANSI 42 and 53 for reduction of the substances listed in the matrix below. The volume, flowrate and capacity has been calculated for ULTF4PLUS utilizing the operating and lab test data from the ULTRAFILTR10PLUS and ULTRAFILTR20PLUS units, as the filter systems are identical other than larger size of the ULTF4PLUS unit. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42 and 53. While testing was performed under standard laboratory conditions, actual performance may vary. Do not use with water that is microbiologically unsafe or of unknown quality.

NSF/ANSI Standard	Substance or Claim	Influent Challenge Concentration	Standard requirement
42	Particulate, Class 1 Particles 0.5 to <1 µm	At least 10,000 particles/mL	≥ 85% reduction
42	Chlorine	2.0 mg/L ± 10%	≥ 50% reduction
53	Total PFAS*	0.00216 mg/L ± 20%	.00002 mg/L maximum

*The test mixture for total PFAS is made up of PFOA (500 ppt), PFOS (1,000 ppt), PFHxS (300 ppt), PFNA (50 ppt), PFHpA (40 ppt), PFBS (260 ppt), and PFDA (10 ppt).

ULTF4PLUS also complies with NSF/ANSI standards 61 and 372.

After installation, flush the system by running water through the dispenser for approximately 5 minutes.

General Operation: read and follow Owner’s Manual instructions before installation and use of this product. Maintenance requirement for the cartridge: it should be replaced per the capacity listed in the operating parameters (based on the homeowner’s flowrate entering the POE system) for the PFAS reduction, or sooner if a noticeable reduction in flow rate occurs.

The contaminants or other substances removed or reduced by this water filter are not necessarily in all users’ water. The system and installation shall comply with applicable state and local regulations.