

# STAINLESS STEEL FLEXIBLE CORRUGATED CONNECTORS



## Specifications

- ◆ Stainless steel 304 (ASTM A240) CSST
- ◆ Chrome-plated brass Hpb58-3 fittings
- ◆ High-quality EPDM gasket
- ◆ Up to 125 psig working pressure
- ◆ Up to 189 psig intermittent impulse pressure
- ◆ -40°F to 180°F (82°C) temperature
- ◆ 2.5" minimum bend radius
- ◆ 100% leak tested

## Applications

- ◆ Water supply, water softeners, water heaters, etc.

Item No.	Description	Master Carton	Item No.	Description	Master Carton
CFC75X12SS	¾" FIP X ¾" FIP X 12"	25	CFC1X18SS	1" FIP X 1" FIP X 18"	15
CFC75X18SS	¾" FIP X ¾" FIP X 18"	25	CFC1X24SS	1" FIP X 1" FIP X 24"	15
CFC75X24SS	¾" FIP X ¾" FIP X 24"	25	CFC125X18SS	1¼" FIP X 1¼" FIP X 18"	10
CFC75X1X18SS	¾" FIP X 1" FIP X 18"	15	CFC125X24SS	1¼" FIP X 1¼" FIP X 24"	10
CFC75X1X24SS	¾" FIP X 1" FIP X 24"	15	CFC150X18SS	1½" FIP X 1½" FIP X 18"	5
CFC1X12SS	1" FIP X 1" FIP X 12"	15	CFC2X18SS	2" FIP X 2" FIP X 18"	5

