

# E-Z WELD-ON PITLESS ADAPTER



**E-Z WELD-ON PITLESS ADAPTER** - For 4" I.D., 5" I.D., 6" I.D., and 7" O.D. wells.

\*Conforms to Water Systems Council PAS-97(2012)

\*Conforms to NSF/ANSI 372

## FEATURES

- 1" NPT male nipple fabricated from 304 stainless steel
- 304 stainless steel locating support pins
- Steel housing contains a taper located along the bottom of the adapter to allow for easy bottom side welding
- Positive stop feature on the interior housing assures for proper O-ring seal
- 1" NPT female drop fitting fabricated from high quality lead free red brass
- 1600 lb maximum safe load rating
- Chamfered 1" pull pipe port
- Large drainage hole located on the backside of the drop fitting to prevent chlorine build up
- Drop fitting contains a long sweep 90° turn
- Pump is more centrally located within the well
- Large neoprene O-ring
- Factory pressure test to 85 PSI

### E-Z WELD-ON PITLESS ADAPTER

ORDER NO.	WELL SIZE	DROP PIPE SIZE	DISCHARGE PIPE SIZE	WEIGHT	LEAD FREE
6123BEZLF	4" I.D., 5" I.D., 6" I.D., 7" O.D.	1" female NPT	1" male NPT	5.4 lb	YES

