

**NEW**

# STAINLESS STEEL FROST-PROOF HYDRANT

**MAGNUM  
STAINLESS STEEL**



Introducing the Monitor® Stainless Steel Magnum Frost-Proof Hydrant. The new 304 Stainless Steel dry pipe provides a premium level of corrosion resistance, making it an enhanced solution to protect against even the most corrosive soil conditions. The Monitor® Stainless Steel Magnum excelled during 3<sup>rd</sup> party laboratory testing in which it was exposed to over 500 hours of a continuous corrosive salt spray, per ASTM B117.

The unique spool valve design and simple construction of the Monitor® Stainless Steel Magnum hydrant provides dependable operation and easy servicing in any weather. The “Balanced Valve allows smooth easy flow adjustment since the water flow does not oppose valve movement as in other hydrants. Corrosion resistant brass valve body, acetal spool and ¾” Sch. 80 PVC wet pipe contain the water flow, extending hydrant life. The elimination of a packing nut, valve rod, and linkage adjustment eliminates many maintenance and repair kits required with ordinary hydrants. When properly installed, occasional easy replacement of the three standard O-rings will be the only routine maintenance required.

**All internal parts can be quickly removed without the use of pipe wrenches or digging; just turn off water supply, loosen the stainless steel hex screw in the collar, and pull out the wet pipe. Replace the O-ring, then simply bottom out the head casting on the stand pipe. Rotate the head casting outlet (clockwise only) to home owner’s preference and tighten the set screw.**

**Location of outlet is approximately 24” above ground in addition to bury depth.**

### Lead Free Models

Bury Depth	Hydrant	Wt (lb)
1 ft	1WHMB75LFSS	10
1.5 ft	1.5WHMB75LFSS	11
2 ft	2WHMB75LFSS	11
2.5 ft	2.5WHMB75LFSS	12
3 ft	3WHMB75LFSS	13
4 ft	4WHMB75LFSS	14
5 ft	5WHMB75LFSS	15
6 ft	6WHMB75LFSS	17
7 ft	7WHMB75LFSS	18
8 ft	8WHMB75LFSS	19
10 ft	10WHMB75LFSS	22
11 ft	11WHMB75LFSS	26

Bury Depth	Hydrant	Wt (lb)
1 ft	1WHMB75SS	10
1.5 ft	1.5WHMB75SS	11
2 ft	2WHMB75SS	11
2.5 ft	2.5WHMB75SS	12
3 ft	3WHMB75SS	13
4 ft	4WHMB75SS	14
5 ft	5WHMB75SS	15
6 ft	6WHMB75SS	17
7 ft	7WHMB75SS	18
8 ft	8WHMB75SS	19
10 ft	10WHMB75SS	22
11 ft	11WHMB75SS	26

\*LF models Contain less than 0.25% lead as required by NSF/ANSI 372

Baker Mfg. Co., LLC – Baker Water Systems  
133 Enterprise Street Evansville, WI 53536  
800-356-5130 • Fax: 608-882-3777  
[www.bakerwatersystems.com](http://www.bakerwatersystems.com)

